MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC. 430 S. WHEELING ROAD WHEELING, IL 60090

PRODUCT NAME: SLIDE TAP-IT AEROSOL

EMERGENCY TELEPHONE #: 800-535-5053 REVISION DATE: SEPT. 1, 2009 INFORMATION TELEPHONE #: 847-541-7220 PRODUCT NUMBER: 404 BULK FAX NUMBER: 847-541-7986 D.U.N.S. NUMBER: 00-299-4168

PREPARED BY: JIM ARMSTRONG

THIS MSDS IS APPLICABLE TO 40401B, 40405B, & 40455B

SECTION I. IDENTIFICATION

CHEMICAL NAME: SYNTHETIC LUBRICANTS SOLUTION

CHEMICAL FAMILY:SEE ABOVE

FORMULA: 40412

SYNONYMS: SLIDE TAP-IT 1 AND 5 GALLON CONTAINERS

DOT HAZARD CLASSIFICATION: ORM-D

DOT SHIPPING NAME: CONSUMER COMMODITY

CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE

IDENTIFICATION NUMBER: NONE

55 GALLON CONTAINERS

DOT HAZARD CLASSIFICATION: NONE DOT SHIPPING NAME: LUBRICATING OIL NOI

IDENTIFICATION NUMBER: NONE

PACKING GROUP: NONE H.M.I.S. RATING: 1,2,0,B

SECTION II. PHYSICAL DATA

BOILING POINT: 188-190 DEGREES F. FREEZING POINT: <-50 DEGREES F. SPECIFIC GRAVITY: (H20 =1): .84 WEIGHT PER GALLON @ 60 F.: 7.01

VAPOR PRESSURE OF CONCENTRATE @ 70 F. (MM HG: NIL

VAPOR DENSITY (AIR =1): >1

SOLUBILITY IN WATER, % BY WT.: 20 EVAPORATION RATE (MINUTES): >1

APPEARANCE AND ODOR: YELLOW TINT, SLIGHT HYDROCARBON ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:APPROX. WEIGHT%CAS NUMBER:PEL(OSHA)PROPRIETARY LIQUID75-85143-28-2NOT ESTABLISHEDALIPHATIC HYDROCARBON15-2564742-48-9*300 PPM

**CONTAINS NO OZONE DEPLETING CHEMICALS

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: N/A UEL: N/A (VOLUME %)

FLASH POINT: NO FLASH

SPECIAL FIRE FIGHTING PROCEDURES: NONE UNUSUAL FIRE & EXPLOSION HAZARDS: NONE

SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN HAZARDOUS COMBUSTION BY-PRODUCTS: SEE SECTION IV.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: TEMP. ABOVE 120' F.-DIRECT SUNLIGHT

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 300 PPM

EFFECTS OF OVEREXPOSURE

INGESTION (SWALLOWING): N/A

INHALATION: NONE

SKIN CONTACT: DEFATTING OF SKIN EYE CONTACT: TEMPORARY IRRITATION

• EMERGENCY AND FIRST AID PROCEDURES*

SKIN: WASH WITH SOAP AND WATER, APPLY HAND CREAM

INHALATION: REMOVE TO FRESH-AIR LOCATION AWAY FROM EXPOSURE EYES: RINSE WITH PLENTY COOL CLEAN WATER UNTIL IRRITATION SUBSIDES

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.

WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL – CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: (SPECIFY TYPE): NOT NEEDED WITH ADEOUATE VENTILATION

VENTILATION: ADEQUATE VENTILATION RECOMMENDED PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED

EYE PROTECTION: PROPER EYE CARE IS NEEDED IN ALL INDUSTRIAL OPERATIONS

OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM HEAT SOURCES OR DIRECT SUNLIGHT-DO NOT PUNCTURE OR INCINERATE-DO NOT DROP! OTHER PRECAUTIONS: AVOID OVER-SPRAYING ONTO FLOORS OR SLIPPERY SURFACE MAY RESULT.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCTS SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO GE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THSES RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

http://www.slideproducts.com/cutting.htm