MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC. 430 S. WHEELING ROAD WHEELING, IL 60090

PRODUCT NAME: SLIDE ZINC STEARATE 41025

EMERGENCY TELEPHONE: 800-535-5053 INFORMATION TELEPHONE: 847-541-7220

FAX NUMBER: 847-541-7986 PREPARED BY: JIM ARMSTRONG REVISION DATE: SEPT. 1, 2009 PRODUCT NUMBER: 41025 D.U.N.S. NUMBER: 00-299-4168

SECTION I. IDENTIFICATION

CHEMICAL NAME: ZINC STEARATE POWDER CHEMICAL FAMILY: FATTY ACID SOAP

FORMULA: POWDER

SYNONYMS: SLIDE ZINC STEARATE

DOT HAZARD CLASSIFICATION: NON-HAZARDOUS DOT SHIPPING NAME: FATTY ACID SOAP-POWDER CHEMICAL ABSTRACT REGISTRY NUMBER: 557-05-1

IDENTIFICATION NUMBER: 129980-SUB 2

H.M.I.S. RATING: 1,1,0,B

SECTION II. PHYSICAL DATA

BOILING POINT: N/A FREEZING POINT: <.50' F. SPECIFIC GRAVITY (H20=1): 1.00

WEIGHT PER GALLON @ 60 F.: N/A

VAPOR PRESSURE OF CONCENTRATE @ 70 F. (MM HG): N/A

VAPOR DENSITY (AIR =1): N/A

SOLUBILITY IN WATER, % BY WT.: NEGLIGIBLE

PERCENT VOLATILE BY WEIGHT: N/A EVAPORATION RATE (MINUTES): N/A

APPEARANCE AND ODOR: FINE WHITE POWDER, MILD FATTY ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL: APPROX. WEIGHT %: CAS NUMBER: PEL(OSHA):

ZINC STEARATE 100.0 557-05-1 N/A

**CONTAINS NO OZONE DEPLETING CHEMICALS **

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: >500.'F (PMCC)

FLASH POINT: N/A

EXTINGUISHING MEDIA: WATER, CO2, FOG, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: N/A

UNUSUAL FIRE & EXPLOSION HAZARDS: A FINE DUST IN AIR, IT MATY BE A HAZARD WITH AN IGNITION SOURCE.

SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS

HAZARDOUS COMBUSTION BY-PRODUCTS: CO2 AND ZnO HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: N/A

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 10 mg/m3

EFFECTS OF OVEREXPOSURE *

INGESTION (SWALLOWING): N/A

INHALATION: MAY CAUSE LUNG IRRITATION AND LUNG TISSUE IRRITATION

SKIN CONTACT: N/A

EYE CONTACT: TEMPORARY IRRITATION

• EMERGENCY AND FIRST AID PROCEDURES *

SKIN: WASH WITH SOAP AND WATER

INHALATON: REMOVE TO FRESH AIR LOCATION

EYES: FLUSH WITH PLENTY OF WATER, CALL PHYSICIAN IMMEDIATELY.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE IGNITION SOURCES, SHOVEL INTO DRUMS

WASTE DISPOSAL METHOD: DISPOSE OF CONSISTENT WITH LOCAL, STATE, AND FEDERAL REGS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): RESPIRATOR IF USED ROUTINELY

VENTILATION: ADEQUATE VENTILATION NEEDED

PROTECTIVE GLOVES: RUBBER GLOVES RECOMMENDED BUT NOT REQUIRED

EYE PROTECTON: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS

OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM DIRECT SUNLIGHT, BELOW 120' F.

SECTION X. CARCINOGENIC HAZARD

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARU, N.T.P., OSHA OR ACGIH.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THSES RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

http://www.slideproducts.com/mold.htm