

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.
430 S. WHEELING ROAD
WHEELING, IL 60090

PRODUCT NAME: SLIDE PLASTIC CLEANER WITH FOAMACTION

EMERGENCY TELEPHONE #: 800-535-5053
INFORMATION TELEPHONE: 847-541-7220
FAX NUMBER: 847-541-7986
PREPARED BY: JIM ARMSTRONG

REVISION DATE: SEPT. 1, 2009
PRODUCT NUMBER: 41515
D.U.N.S. NUMBER: 00-299-4168

SECTION I. IDENTIFICATION

CHEMICAL NAME: MIXTURE
CHEMICAL FAMILY:
FORMULA: 41515
SYNONYMS: SLIDE PLASTIC/GLASS CLEANER
DOT HAZARD CLASSIFICATION: ORM-D
DOT SHIPPING NAME: CONSUMER COMMODITY
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE
IDENTIFICATION NUMBER: NONE
H.M.I.S. RATING: 1,1,0,A

SECTION II. PHYSICAL DATA

BOILING POINT: N/A
FREEZING POINT: 32° F.
SPECIFIC GRAVITY (H2O =1): <1.0
WEIGHT PER GALLON @ 60 F.: 7.84
VAPOR PRESSURE OF CONCENTRATE @ 130 F. (MM HG): 140
VAPOR DENSITY (AIR=1): >1
SOLUBILITY IN WATER, % BY WT.: 5-25 %
EVAPORATION RATE (ETHER =1): <1
APPEARANCE AND ODOR: SEMI-STABLE FOAM WITH FLORAL ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:	APPROX. WEIGHT %:	CAS NUMBER:	PEL(OSHA)
2-BUTOXYETHANOL	1-10	111-76-2	25 PPM
EHTYL ALCOHOL	4-20	64-17-5	1000 PPM
METHYL ALCOHOL	<1.0	67-56-1	200 PPM
DEIONIZED WATER	70-90	N/A	N/A
LIQUIFIED PETROLEUM GAS	1-5	68476-85-7	1000 PPM

CONTAINS NO OZONE DEPLETING CHEMICALS

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: 1.8 UEL: 9.2 (VOLUME %)
FLASH POINT: N/A
AEROSOL FLAME PROJECTION TEST: NON-FLAMMABLE AS DETERMINED BY THE AEROSOL FLAME PROJECTION TEST DESCRIBED IN 16 CFR 1500.45
EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, FOAM, AND DRY CHEMICAL
SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT TEMPERATURES ABOVE 120 DEGREES F.

SECTION V. REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS, HEAT AND OPEN FLAME
HAZARDOUS COMBUSTION BY-PRODUCTS: CARBON MONOXIDE AND CO2 MAY BE FORMED
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: OPEN FLAMES AND HIGH TEMPERATURES

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 25 PPM

• **EFFECTS OF OVEREXPOSURE ***

INGESTION (SWALLOWING): LARGE QUANTITIES MAY RESULT IN RED BLOOD CELL HEMOLYSIS
INHALATION: EXCESSIVE INHALATION CAN PRODUCE RESPIRATORY IRRITATION
SKIN CONTACT: CONCENTRATED SPRAY MAY CAUSE DRYING, IRRITATION AND DERMATITIS
EYE CONTACT: TEMPORARY BURNING AND IRRITATION

• **EMERGENCY AND FIRST AID PROCEDURES ***

SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER
INHALATION: REMOVE TO FRESH AIR LOCATION AND PROVIDE OXYGEN IF BREATHING IS
DIFFICULT.
EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES WHILE HOLDING EYELID OPEN
INGESTION: CALL LOCAL POISON CONTROL CENTER OR PHYSICIAN IMMEDIATELY.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES OF IGNITION
AND VENTILATE AREA. SOAK UP SPILL WITH ABSORBANT MATERIAL.
WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR
INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL
IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION
VENTILATION: ADEQUATE VENTILATION NEEDED
PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED
EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS
OTHER PROTECTIVE EQUIPMENT: AS YOUR COMPANY REQUIRES

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM DIRECT
SUNLIGHT, BELOW 120' F. DO NOT DROP, PUNCTURE OR INCINERATE.
OTHER PRECAUTIONS: DO NOT SPRAY DIRECTLY INTO FLAME. DO NOT SMOKE WHILE USING
PRODUCT. DO NOT SPRAY ON FLOORS.

SECTION X. CARCINOGENIC HAZARD

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARU, N.T.P., OSHA, OR
ACGIH.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT
SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED
INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY
APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE
SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE.
THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE
CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD
COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND
REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

<http://www.slideproducts.com/cleaners.htm>