MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC. 430 S. WHEELING RD. WHEELING, IL 60090

PRODUCT NAME: SLIDE UNIVESAL OIL 42600H

EMERGENCY TELEPHONE: 800-535-5053 INFORMATION TELEPHONE: 847-541-7220 D.U.N.S. NUMBER: 00-299-4168 PREPARED BY: JIM ARMSTRONG

REVISION DATE: SEPT. 1, 2009 PRODUCT NUMBER: 42600H FAX NUMBER: 847-541-7986

SECTION I. IDENTIFICATION

-----CHEMICAL NAME: SEVERELY HYDRO TREATED PARAFFINIC WHITE OIL CHEMICAL FAMILY: MINERAL OIL DERIVATIVE FORMULA: 42600H

SYNONYMS: SLIDE UNIVERSAL

DOT HAZARD CLASSIFICATION: Non-hazardous DOT SHIPPING NAME: Lubricating, NOI CHEMICAL ABSTRACT REGISTRY NUMBER: 8042-47-5 IDENTIFICATION NUMBER: NONE H.M.I.S. RATING: 1,0,0,B

SECTION II. PHYSICAL DATA

DATA IN SECTION II APPLY TO CONCENTRATE BEFORE ADDING PROPELLANT

BOILING POINT: N/A
FREEZING POINT: <-20' F.
SPECIFIC GRAVITY (H20 = 1): 1.05
WEIGHT PER GALLON @ 60 F.: 8.35
VAPOR PRESSURE @ 70 F. (MM HG): NIL
VAPOR DENSITY (AIR = 1): N/A
SOLUBILITY IN WATER, % BY WT.: NIL
PERCENT VOLATILE BY WEIGHT: 0
EVAPORATION RATE (MINUTES): N/A
APPEARANCE AND ODOR: CLEAR OILY

APPEARANCE AND ODOR: CLEÁR, OILY FLUID,

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL: APPROX. WEIGHT %: CAS NUMBER: ALIPHATIC HYDROCARBON 100.0 8042-47-59 **CONTAINS NO OZONE DEPLETING CHEMICALS**
ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY PEL(OSHA):

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

(VOLUME %)

FLAMMABLE LIMITS IN AIR: LEL: UEL: (VOLUM FLASH POINT: N/A AEROSOL FLAME PROJECTION TEST: N/A EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, FOAM PARAGRAPH 191.15 SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS UNUSUAL FIRE & EXPLOSION HAZARDS:

SECTION V. REACTIVITY DATA

STABILITY: STABLE INCOMPATIBILITY (MATERIALS TO AVOID): N/A HAZARDOUS COMBUSTION BY-PRODUCTS: HAZARDOUS POLYMERIZATION: WILL NOT OCCUR CONDITIONS TO AVOID: N/A

SECTION VI. HEALTH HAZARD DATA

-----THRESHOLD LIMIT VALUE: N/A

* EFFECTS OF OVEREXPOSURE *

INGESTION (SWALLOWING): PRODUCT IS APPROVED AS A DIRECT FOOD ADDITIVE

INHALATION:

SKIN CONTACT: NO HARM TO SKIN EYE CONTACT: TEMPORARY IRRITATION, RINSE WILL COOL AND CLEAN WATER

* EMERGENCY AND FIRST AID PROCEDURES *

SKIN: WASH WITH SOAP AND WATER

INHALATION:

EYES: FLUSH WITH PLENTY OF WATER.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.

WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING, DO NOT PUNCTURE OR INCINERATE. CAN BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION VENTILATION: ADEQUATE VENTILATION NEEDED PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS OTHER PROTECTIVE EQUIPMENT: AS YOUR COMPANY REQUIRES.

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM DIRECT SUNLIGHT, BELOW 120' F. DO NOT DROP, PUNCTURE, OR INCINERATE. OTHER PRECAUTIONS: DO NOT SMOKE WHILE USING PRODUCT. DO NOT SPRAY ON FLOORS.

SECTION X. CARCINOGENIC HAZARD

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARU, N.T.P., OSHA, OR ACGIH.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.