MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC. 430 S. WHEELING ROAD WHEELING, IL 60090

PRODUCT NAME: BULK ECONO-SPRAY MOLD CLEANER

EMERGENCY NUMBER: 800-535-5053 REVISION DATE: SEPT. 1, 2009 INFORMATION NUMBER: 847-541-7220 PRODUCT NUMBER: 456 BULK FAX NUMBER: 847-541-7986 D.U.N.S. NUMBER: 002-299-4168

PREPARED BY: JIM ARMSTRONG

THIS MSDS IS APPLICABLE TO: 45601B, 45605B, and 45655B UNITS

SECTION I. IDENTIFICATION

CHEMICAL NAME: ALIPHATIC HYDROCARBON

CHEMICAL FAMILY: ORGANIC FORMULA: 45601B, 45605B, and 45655B SYNONYMS: DEGREASER SOLVENT SPRAY DOT HAZARD CLASSIFICATION: ORM-D

DOT SHIPPING NAME: CONSUMER COMMODITY

CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE

IDENTIFICATION NUMBER: NONE

H.M.I.S. RATING: 1,2,0,B

1 & 5 GALLON SHIPPING INFORMATION:

DOT CLASSIFICATION: NOT REGULATED BY DOT IN CONTAINERS < 119 GALLONS

DOT SHIPPING NAME: ORM-D

ID NUMBER: NONE PACKING GROUP: NONE

55 GALLON SHIPPING INFORMATION:

DOT CLASSIFICATION: NOT REGULATED BY DOT IN CONTAINERS< 119 GALLONS

DOT HAZARD CLASSIFICATION: COMBUSTIBLE LIQUID DOT SHIPPING NAME: COMBUSTIBLE LIQUID, NOS

ID NUMBER: NA 1993 PACKING GROUP: III

SECTION II. PHYSICAL DATA

BOILING POINT: 160-174 DEGREES F.

FREEZING POINT: -25'F.

SPECIFIC GRAVITY (H20 =1): .748

VAPOR PRESSURE OF CONCENTRATE @ 70 F. (MM HG): 14

VAPOR DENSITY (AIR = 1): >1

SOLUBILITY IN WATER, % BY WT.: NIL PERCENT VOLATILE BY WEIGHT: 100 EVAPORATION RATE (MINUTES): 20

APPEARANCE AND ODOR: CLEAR COLORLESS, SLIGHT HYDROCARBON ODOR

SECTION III, HAZARDOUS INGREDIENTS

MATERIAL: APPROX. WEIGHT % CAS NUMBER: TLV(UNITS):
ALIPHATIC HYDROCARBON 100 64742-48-9* 300 PPM

##CONTAINS NO OZONE DEPLETING CHEMICALS##

ALL COMPONENTS OF THIS PRODUCT ARE LISTED IN THE TSCA DIRECTORY

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: 1.2 UEL:9.6

FLASH POINT: 104 DEGREES F (C.C.)

EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, FOAM

SPECIAL FIRE FIGHTING PROCEDURES: FIRE FIGHTERS SHOULD BE EQUIPPED WITH SELF CONTAINING BREATHING APPARATUS.

SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN HAZARDOUS COMBUSTION BY-PRODUCTS: CO, CO2, H2O

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: OPEN FLAMES AND HIGH TEMPERATURES

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 300 PPM

EFFECTS OF OVEREXPOSURE

INGESTION (SWALLOWING): NAUSEA

INHALATION: HEADACHES, NAUSEA, DIZZINES, DECREASED BLOOD PRESSURE

SKIN CONTACT: DEFATTING AND DRYING OF SKIN. ALLERGIC REACTIONS ARE POSSIBLE

EYE CONTACT: IRRITATION, TEARING, REDDENING, OR SWELLING.

EMERGENCY AND FIRST AID PROCEDURES

SKIN: WASH WITH SOAP AND WATER. CALL PHYSICIAN IF IRRITATION PERSISTS INHALATION: REMOVE TO FRESH-AIR LOCATION. PROVIDE OXYGEN IF NEEDED. EYES: FLUSH WITH COOL CLEAN WATER. CALL PHYSICIAN IF IRRITATION PERSISTS.

INGESTION: DO NOT INDUCE VOMITING!! GIVE A GLASS OF WATER OR MILK. CALL PHYSICIAN.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.

WASTE DISPOSAL METHOD: DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION

VENTILATION: ADEQUATE VENTILATION NEEDED

PROTECTIVE GLOVES: NOT REQUIRED BUT RECOMMENDED

EYE PROTECTION: SAFETY GLASSED SHOULD ALWAYS BE WORN IN AN INDUSTRIAL OPERATION.

OTHER PROTECTIVE EQUIPMENT: NOT NORMALLY REQUIRED.

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS, AWAY FROM HEAT OR DIRECT SUNLIGHT ABOVE 120' F. KEEP AWAY FROM IGNITION SOURCES.
OTHER PRECAUTIONS: DO NOT DROP. DO NOT SPRAY NEAR OPEN FLAMES. DO NOT PUNCTURE OR INCINERATE EMPTY OR FULL CONTAINERS.

SECTION X.

NO CHEMICALS IN THIS PRODUCTS ARE CURRENTLY LISTED AS CARCINOGENS.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCTS SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.